

mosHTML::PrintIcon

Last Updated Thursday, 26 October 2006

Last reviewed: Not reviewed

phpDocumentor

mosHTML::PrintIcon

Displays a standard print icon. The alternative text for the icon will be taken from the current language settings.
Syntax

```
void PrintIcon ( int &$row, object &$params, boolean $enable, string $link [, string $window_params] )
```

`$row` is the row index.

`$params` is an object of type `mosParameters`. If `$params->get('print')` is false then this function will produce no output. If `$params->get('popup')` is true then the icon will be a print icon; if false it will be a print preview icon. If `$params->get('icons')` is true then the print button will be in the form of an image; if false it will be a text link.

`$hide_js` is a flag. If true then this function will produce no output.

`$link` is the complete URI of the resource to be printed or print previewed.

`$window_params` is a string containing the window parameters that will be used for the popup print preview window. This parameter is optional and if omitted will default to `'status=no, toolbar=no, scrollbars=yes, titlebar=no, menubar=no, resizable=yes, width=640, height=480, directories=no, location=no'`.

Examples

Example: In this example the popup window that will be opened if the print icon is clicked will make use of the standard window parameters.

```
// Set-up the parameters object.
```

```
$params = & new mosParameters( " );
```

```
$params->def( 'print', true );
```

```
$params->def( 'popup', true );
```

```
$params->def( 'icons', true );
```

```
// Set-up the URL that will be opened if the print icon is clicked.
```

```
$url = $mosConfig_live_site . '/index2.php?option=com_content&task=view&id=' .
```

```
    $row->id . '&Itemid=' . $Itemid;
```

```
// Draw the Print icon.
```

```
mosHTML::PrintIcon( $row, $params, false, $url );
```

Please report any errors on this page to the [Developer Documentation Forum](#).