

[REVIEW] database->getTableCreate

Last Updated Sunday, 24 December 2006

Last reviewed: Not reviewed

phpDocumentor database->getTableCreate

Generates the SQL code that would be required to create new (empty) tables exactly like the ones specified. Returns an array of SQL 'CREATE TABLE' statements.

Syntax

array getTableCreate (array \$tables) \$tables is an array of table names for which SQL statements are to be generated.

Examples

```
Example:
function generateSQL() {
    global $database;

    $prefix = $database->_table_prefix;
    $tables = array( $prefix.'content_frontpage', $prefix.'content_rating' );
    $result = $database->getTableCreate( $tables );
    print_r( $result );
}
```

generateSQL();

might produce:

Array

```
(
    [jos_content_frontpage] => Array
    (
        [0] => CREATE TABLE `jos_content_frontpage` (
`content_id` int(11) NOT NULL default '0',
`ordering` int(11) NOT NULL default '0',
PRIMARY KEY (`content_id`)
) TYPE=MyISAM

        [jos_content_rating] => Array
        (
            [0] => CREATE TABLE `jos_content_rating` (
`content_id` int(11) NOT NULL default '0',
`rating_sum` int(11) unsigned NOT NULL default '0',
`rating_count` int(11) unsigned NOT NULL default '0',
`lastip` varchar(50) NOT NULL default "",
PRIMARY KEY (`content_id`)
) TYPE=MyISAM

    )
)
```

Please report any errors on this page to the Developer Documentation Forum.